

# OA6-24

## 24V Control Board

The OA6-24 control board is designed to control multiple 24vac solenoid valves.

It provides an easy and efficient method to control up to 6 valves ... each with individual timer settings. Up to 5 OA6-24 can be connected to a single Aqua-x providing a maximum of 30 individually controlled outputs to connect to your solenoid valves.

The Aqua-x can also provide a "master pump link" by using a DSP-1 along with the OA6-24. Connecting a DSP-1 to the OA6-24 provides an automatic "pump link" between the DSP-1 and the OA6-24. When any of the 24vac irrigation zones are activated on the OA6-24, the DSP-1 will automatically turn on the pump.



## Specifications

### OA6-24

#### Input Voltage

**Voltage** 110-240 VAC

#### Max Output Current

**Voltage/Current** 24VAC/0.2A per output

#### Max Input Current

**Holding Current** 0.2A

**Inrush Current** 400ma

#### Package Dimensions

**Size** 10.83inch / 275mm(L) x  
6.46inch / 164mm(W) x  
1.58inch / 40mm(H)

#### Working Environments

**Temperature** 32-104°F (0-40°C)

**Humidity** ≤90%HR

#### Package Content

**24V Control Board** 1pc

**16ft RJ12 Cable** 1pc

**Gross Weight** 1.34lbs / 0.61kg

## Link Up

### OA6-24

#### CONNECTION DIAGRAM

